

eero PoE 6

Dual-band Wi-Fi 6 PoE access point.



Wired connections ensure greater reliability and performance compared to wireless connections.

With the included bracket, the eero PoE 6 can be easily mounted to ceilings or walls for maximum coverage. Sets up in minutes after installation.

Part of eero's PoE line, eero PoE 6 works seamlessly with eero PoE Gateway, a wired eero router and 10-port, PoE+ smart network switch in one device.

PACKAGING INCLUDES

One eero PoE 6, one mounting bracket, and mounting accessories.



OPTIONAL ACCESSORIES

eero 15W USB-C PSU and eero CAT6a Ethernet cables.

TOP PRODUCT BENEFITS



High-speed wifi

Wireless client speeds up to 1.6 Gbps provide a consistent streaming, gaming, and working experience in every part of a home or business.



Wired solution for highly connected homes

eero PoE 6 is ideal for creating a wired network that can support 100+ devices—with each access point covering up to 2,000 sq. ft. It's mountable, can be powered by a 15W power supply unit or by PoE, and can be set up as the gateway for the network or as a leaf for extending coverage.



Experience the eero TrueMesh difference

Our TrueMesh technology intelligently routes traffic to reduce drop-offs so you can confidently stream 4K video, game, and video conference.



Manage it all remotely

Set up, manage, view, and troubleshoot all your customers' networks in the eero app. Home or business network owners get the award-winning consumer app experience that's made eero a leader.



Gets better over time

Automatic updates bring you the latest features and help keep your network safe and secure.



World-class customer support

Our highly trained support team is ready to help resolve any wifi issues by email at support@eero.com or by phone in the U.S. at +1-877-659-2347.

For more information, visit eero.com

©2024 Amazon.com, Inc. or its affiliates. Amazon, eero, and all related marks are trademarks of Amazon.com, Inc. or its affiliates.

eero

The way wifi should be.

eero PoE 6



TECHNICAL SPECIFICATIONS

Wireless and Ethernet

Wi-Fi specifications

Wi-Fi 6 (IEEE 802.11a/b/g/n/ac/ax)
2x2 2.4 GHz (574 Mbps peak)
2x2 5 GHz (2402 Mbps peak)
AX3000

Wifi features

Automatic channel selection
Band and client steering
WMM, OFDMA, SU-MIMO

Frequency bands

ISM (2.4-2.484 GHz)
U-NII-1 (5.15-5.25 GHz)
U-NII-2A (5.25-5.35 GHz, DFS)
U-NII-2C (5.47-5.725 GHz, DFS)
U-NII-3 (5.725-5.85 GHz)
U-NII-4 (5.85-5.925 GHz)

Ethernet

One auto-sensing 2.5 GbE,
PoE-capable port
One auto-sensing 1 GbE port

Services and smart home

Network security and services

WPA2, WPA3, TLS v1.2+, VPN passthrough,
IPv6, NAT, UPnP, port forwarding, DHCP,
static IP, and cloud connectivity

Smart home hub

Thread, Zigbee, Matter (controller only),
Bluetooth Low Energy 5.0, Works with Alexa,
and Amazon Connected Home

Management tools

iOS & Android apps
Parental Controls
Password sharing
eero Insight

Compatible subscription services*

eero Plus
eero for Business
eero for Service Providers

Physical characteristics and power

Actual size and weight may vary by manufacturing process.

Size

6.45 x 6.45 x 1.7 in.
(163.8 x 163.8 x 43 mm)

Weight

1.04 lbs. (473 g)

Operating temperature

32°F-104°F (0°C-40°C)

Power

Requires up to 15W over PoE 802.3bt or
802.3af
Compatible with eero power supply units
15W and higher, 100-240V AC, 50/60 Hz

Warranty

1-year limited warranty

Works with Alexa not available in all countries. eero PoE 6 and services, including eero subscription services, are subject to the disclaimers found at eero.com/disclaimers
*Additional services each require a separate subscription.

For more information, visit eero.com
For pro installer details, visit pro.eero.com

©2024 Amazon.com, Inc. or its affiliates. Amazon, eero, and all related marks are trademarks of Amazon.com, Inc. or its affiliates.

eero
The way wifi should be.